



MiniRAE 3000

Portable Handheld VOC Monitor

The MiniRAE 3000 is the most advanced handheld volatile organic compound (VOC) monitor on the market. Its photoionization detector's (PID) extended range of **0 to 15,000 ppm** makes it an ideal instrument for applications from industrial hygiene to leak detection and HazMat.

The **RF modem allows real-time data transmissions** with a base controller located up to 500 feet away from the MiniRAE 3000 (or two miles with optional RAELink3 portable modem). A personal computer can be used as the base station for a MiniRAE 3000 system. The standard ProRAE Remote software is capable of monitoring the input of up to 64 remotely located monitors, including MiniRAE 3000, AreaRAE, etc.



Key Features

• Proven PID technology

The patented sensor provides the following unique features:

- 3-second response time
- Extended range up to 15,000 ppm with improved linearity
- Humidity compensation with integral humidity and temperature sensors

• Real-time wireless data transmission with built-in RF modem or Bluetooth

• Designed for simple service Easy access to lamp and sensor in seconds without tools

• Big graphic display for easy overview of gas type, Correction Factor and concentration

• Field-interchangeable battery pack replaced in seconds without tools

• Integrated flashlight for better view in dark conditions

• User-friendly screens, including dataplot chart view

• Integrated RAE Systems Correction Factors list for more than 200 compounds to measure more chemicals than any other PID

• Multi-language support with 12 languages encoded

• Rugged housing withstands use in harsh environments

- IP67 waterproof design for easy cleaning and decontamination in water
- Strong protective removable rubber boot

Additional Advantages

- View real-time sensor data and alarm status at headquarters or command center
- Automatic lamp type recognition
- Duty-cycling™ lamp and sensor auto-cleaning technology
- Tough, flexible inlet Flexi-Probe™
- 3 large keys operable with 3 layers of gloves
- Strong, built-in sample pump draws up to 100 feet (30m) horizontally or vertically
- Loud, 95dB audible alarm
- Bright red flashing visual alarm
- Interchangeable drop-In lithium-ion and alkaline battery packs
- Charging cradle doubles as an external battery charger
- Compatible with AutoRAE™ calibration station
- ProRAE Remote software simultaneously controls and displays readings for up to 64 remote detectors
- License-free, ISM band RF transmission with communication range up to 500 feet (2 miles with optional RAELink3 modem)
- Optional RAELink3 modem provides GPS capability to track and display readings from remote detectors and provide up to 2 miles' long-distance transmission
- Datalogging with up to 6 months of data at one-minute intervals
- 3-year 10.6eV lamp warranty



ver1_06.07

www.raesystems.com



ATEX



IECEX



MiniRAE 3000

Specifications*

Detector Specifications

Size	10" L x 3.0" W x 2.5" H (25.5 cm x 7.6 cm x 6.4 cm)
Weight	26 oz (738 g)
Sensors	Photoionization sensor with standard 10.6 eV or optional 9.8 eV or 11.7 eV lamps
Battery	<ul style="list-style-type: none">• Rechargeable, external field-replaceable Lithium-Ion battery pack• Alkaline battery adapter
Operating Hours	16 hours of operation (12 hours with alkaline battery)
Display Graphic	4 lines, 28 x 43 mm, with LED backlight for enhanced display readability
Keypad	1 operation and 2 programming keys, 1 flashlight on/off
Direct Readout	<ul style="list-style-type: none">• Instantaneous reading• VOCs as ppm by volume• High values• STEL and TWA• Battery and shutdown voltage• Date, time, temperature
Alarms	<ul style="list-style-type: none">• 95 dB (at 30 cm) buzzer and flashing red LED to indicate exceeded preset limits• High: 3 beeps and flashes per second• Low: 2 beeps and flashes per second• STEL and TWA: 1 beep and flash per second• Alarms latching with manual override or automatic reset• Additional diagnostic alarm and display message for low battery and pump stall
EMI/RFI	Highly resistant to EMI/RFI Compliant with EMC Directive 89/336/EEC
IP Rating	<ul style="list-style-type: none">• IP67 unit off and without flexible probe• IP65 unit running
Datalogging	Standard 6 months at one-minute intervals
Calibration	Two-point or three-point calibration for zero and span. Calibration memory for 8 calibration gases, alarm limits, span values and calibration dates
Sampling Pump	<ul style="list-style-type: none">• Internal, integrated flow rate at 500 cc/mn• Sample from 100' (30m) horizontally and vertically
Low Flow Alarm	<ul style="list-style-type: none">• Auto pump shutoff at low-flow condition
Communication	<ul style="list-style-type: none">• Download data and upload instrument set-up from PC through charging cradle or optional Bluetooth™• Wireless data transmission through built-in RF modem
Frequency	902 to 928 MHz (license-free), 2.400 to 2.4835 GHz (license-free), 433 MHz, 869 MHz
RF Range	Up to 500' (900 MHz, 433 Mhz, 869 Mhz), extendable with RAELink3 Repeater to 2 miles
Hazard Area Approval	<ul style="list-style-type: none">• US and Canada: UL, cUL, Classified as Intrinsically Safe for use in Class I, Division I Groups A, B, C, D• Europe: ATEX II 1G EEx ia IIC T4 (pending)• IECEx: II 1G EEx ia IIC T4 (pending)
Temperature	-4° to 113° F (-20° to 50° C)
Humidity	0% to 95% relative humidity (non-condensing)
Attachments	Durable bright yellow rubber boot with belt clip
Warranty	Lifetime on non-consumable components (per RAE Systems Standard Warranty), 3-year warranty for 10.6 eV lamp, 1 year for pump and battery

*Specifications are subject to change

Sensor Specifications

Gas Monitor	Range	Resolution	Response Time T90
VOCs	0 to 999.9 ppm 1000 to 15,000 ppm	0.1 ppm 1 ppm	< 3 s < 3 s

Monitor only includes:

- MiniRAE 3000 Monitor, Model PGM-7320
- Wireless communication module built in, as specified
- Datalogging with ProRAE Studio Package for Windows™ 95, 98, 2000, NT, ME & XP
- Charging/download adapter
- RAE UV lamp, as specified
- Flex-I-Probe™
- External filter
- Rubber boot
- Alkaline battery adapter
- Lamp-cleaning kit
- Tool kit
- Operation CD-ROM
- Operation & Maintenance manual
- Soft leather case

Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- Charging/download cradle
- 5 Porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

Optional calibration kit adds:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

Optional Guaranteed Cost of Ownership Program:

- 4-year repair and replacement guarantee
- Annual maintenance service

DISTRIBUTED BY:

ver1_06.07

RAE Systems Inc.
3775 North First Street
San Jose, CA 95134 USA
raesales@raesystems.com

USA/Canada 1-877-723-2878
Europe/Russia +45 8652 5155
Middle East/Australia 971 50 429 1385
China 8610 58858788
Asia +852 2669 0828

www.raesystems.com

